




**iSECURE**  
securing identities

## HID AERO X1100 | Master Controller.




### Features :

- Network controller.
- User/card capacity: 250000.
- Transaction memory: 50000.
- Inputs: 07.
- Outputs: 04.
- Wigand reader: 02.
- OSDP readers: 04.

Acti  
Go to



## HID AERO X100 | Reader interface.



### Features :

- Reader interface.
- Connectivity: RS-485.
- Inputs: 07.
- Outputs: 04.
- Wigand reader: 02.
- OSDP readers: 04.
- Addressing type: DIP Switch.
- Distance: Max 1.2KM.



**iSECURE**  
securing identities

## HID - Aero X200 | Input interface.



### Features :

- Input interface.
- Inputs: 19.
- Connectivity: RS-485.
- Addressing type: DIP Switch.
- Distance: Max 1.2KM.



**iSECURE**  
securing identities

## HID AERO X300 | Output interface.




### Features :

- Output interface.
- Outputs: 12.
- Connectivity: RS-485.
- Addressing type: DIP Switch.
- Distance: Max 1.2KM.

# Connectivity schematics



**iSECURE**  
securing identities




**Setup For Wigand Reader**

**Setup For 2 Doors With OSDP Reader**







Note: EM lock and Hooter negative cable will connect to 12VDC minus connection and from SMPS + need to connect in relay-1 and relay-2 C connection.

## Connectivity schematics for OSDP reader



**iSECURE**  
securing identities

## HID EDGE EH400-K




### **Features :**

- Single Door controller.
- Network controller.
- POE support.
- User/card capacity: 250000.
- Transaction memory: 99999.
- Inputs: 05.
- Outputs: 02.
- Wigand reader: 02 can connect.

# Connectivity Schematics For EDGE Controllers



**iSECURE**  
securing identities



## HID SIGNO 25B



**iSECURE**  
securing identities



### Features :

- Cards supported: iclass, SEOS, Mifare, Mobile credentials.
- Network controller standalone.
- Environmental Rating: IP67.
- User/card capacity: 250000.
- Transaction memory: 100000.
- Max user: 5000(1:N)

# Other integrated Biometrics- VIRDI



**iSECURE**  
securing identities



AC5000



AC2100



U bio-x face



U bio-x pro-2



U bio-x pro lite

## Other integrated Biometrics- IDEMIA



**iSECURE**  
securing identities



Idemia MorphoWave™  
Compact



MA Sigma Lite+  
Bio With Screen



Morpho Visionpass  
MDPI

Other integrated Biometrics-  
Suprema



Compact  
fingerprint reader



Suprema  
Facestation 2



**iSECURE**  
securing identities



Suprema FL-DB

# Other integrated Biometrics- EssL/ZK Teco



**iSECURE**  
securing identities



X990



Uface-302



ZkTeco-K30



AI-Face





**iSECURE**  
securing identities

## i access-10 | UHF reader




### **Features :**

- Read range up to 12 meters.
- Compact Design.
- Integrated with all HID Controllers.
- Read Range Adjustment.
- Easy Installation.
- Wigand Connectivity for easy integration.
- Low Power Consumption.



Master Control Centre



UHF Reader 1

[i access-10 | UHF reader | connectivity.](#)